

Alibaba Cloud Apsara Stack Enterprise

Glossary

Version: 2001, Internal: V3.11.0

Issue: 20200424

Legal disclaimer









Alibaba Cloud reminds you to carefully read and fully understand the terms and conditions of this legal disclaimer before you read or use this document. If you have read or used this document, it shall be deemed as your total acceptance of this legal disclaimer.

1. You shall download and obtain this document from the Alibaba Cloud website or other Alibaba Cloud-authorized channels, and use this document for your own legal business activities only. The content of this document is considered confidential information of Alibaba Cloud. You shall strictly abide by the confidentiality obligations. No part of this document shall be disclosed or provided to any third party for use without the prior written consent of Alibaba Cloud.
2. No part of this document shall be excerpted, translated, reproduced, transmitted, or disseminated by any organization, company, or individual in any form or by any means without the prior written consent of Alibaba Cloud.
3. The content of this document may be changed due to product version upgrades, adjustments, or other reasons. Alibaba Cloud reserves the right to modify the content of this document without notice and the updated versions of this document will be occasionally released through Alibaba Cloud-authorized channels. You shall pay attention to the version changes of this document as they occur and download and obtain the most up-to-date version of this document from Alibaba Cloud-authorized channels.
4. This document serves only as a reference guide for your use of Alibaba Cloud products and services. Alibaba Cloud provides the document in the context that Alibaba Cloud products and services are provided on an "as is", "with all faults" and "as available" basis. Alibaba Cloud makes every effort to provide relevant operational guidance based on existing technologies. However, Alibaba Cloud hereby makes a clear statement that it in no way guarantees the accuracy, integrity, applicability, and reliability of the content of this document, either explicitly or implicitly. Alibaba Cloud shall not bear any liability for any errors or financial losses incurred by any organizations, companies, or individuals arising from their download, use, or trust in this document. Alibaba Cloud shall not, under any circumstances, bear responsibility for any indirect, consequential, exemplary, incidental, special, or punitive damages, including lost profits arising from the use or trust in this document, even if Alibaba Cloud has been notified of the possibility of such a loss.
5. By law, all the contents in Alibaba Cloud documents, including but not limited to pictures, architecture design, page layout, and text description, are intellectual property of Alibaba Cloud and/or its affiliates. This intellectual property includes, but is not limited to, trademark rights, patent rights, copyrights, and trade secrets. No part of this document shall be used, modified,

reproduced, publicly transmitted, changed, disseminated, distributed, or published without the prior written consent of Alibaba Cloud and/or its affiliates. The names owned by Alibaba Cloud shall not be used, published, or reproduced for marketing, advertising, promotion, or other purposes without the prior written consent of Alibaba Cloud. The names owned by Alibaba Cloud include, but are not limited to, "Alibaba Cloud", "Aliyun", "HiChina", and other brands of Alibaba Cloud and/or its affiliates, which appear separately or in combination, as well as the auxiliary signs and patterns of the preceding brands, or anything similar to the company names, trade names, trademarks, product or service names, domain names, patterns, logos, marks, signs, or special descriptions that third parties identify as Alibaba Cloud and/or its affiliates.

- 6.** Please contact Alibaba Cloud directly if you discover any errors in this document.

Document conventions

Style	Description	Example
	A danger notice indicates a situation that will cause major system changes, faults, physical injuries, and other adverse results.	 Danger: Resetting will result in the loss of user configuration data.
	A warning notice indicates a situation that may cause major system changes, faults, physical injuries, and other adverse results.	 Warning: Restarting will cause business interruption. About 10 minutes are required to restart an instance.
	A caution notice indicates warning information, supplementary instructions, and other content that the user must understand.	 Note: If the weight is set to 0, the server no longer receives new requests.
	A note indicates supplemental instructions, best practices, tips, and other content.	 Note: You can use Ctrl + A to select all files.
>	Closing angle brackets are used to indicate a multi-level menu cascade.	Click Settings > Network > Set network type .
Bold	Bold formatting is used for buttons, menus, page names, and other UI elements.	Click OK .
Courier font	Courier font is used for commands.	Run the <code>cd /d C:/window</code> command to enter the Windows system folder.
<i>Italic</i>	Italic formatting is used for parameters and variables.	<code>bae log list --instanceid Instance_ID</code>
[] or [a b]	This format is used for an optional value, where only one item can be selected.	<code>ipconfig [-all -t]</code>
{ } or {a b}	This format is used for a required value, where only one item can be selected.	<code>switch {active stand}</code>

Contents

Legal disclaimer.....	I
Document conventions.....	I
Glossary.....	1
A.....	1
B.....	8
C.....	11
D.....	16
E.....	24
F.....	27
G.....	29
H.....	30
I.....	32
J.....	36
K.....	36
L.....	38
M.....	41
N.....	44
O.....	45
P.....	47
Q.....	52
R.....	52
S.....	58
T.....	65
U.....	69
V.....	69
W.....	71
Z.....	72

Glossary

[A](#) | [B](#) | [C](#) | [D](#) | [E](#) | [F](#) | [G](#) | [H](#) | [I](#) | [J](#) | [K](#) | [L](#) | [M](#) | [N](#) | [O](#) | [P](#) | [Q](#) | [R](#) | [S](#) | [T](#) | [U](#) | [V](#) | [W](#) | [Z](#)

A

AccessKey

The AccessKey ID and AccessKey secret that are used in the identity authentication of visitors. The OSS service authenticates the request sender's identity through the symmetrical encryption method of AccessKey ID and AccessKey secret. The AccessKey ID labels the user, and the AccessKey secret encrypts the signed character string and is also the secret key of signed character string of OSS. Between AccessKey ID and AccessKey secret, the AccessKey secret must be encrypted.

AK

additional read throughput

The actually consumed read throughput that exceeds the reserved read throughput. The statistics are collected per second.

additional write throughput

The actually consumed write throughput that exceeds the reserved write throughput. The statistics are collected per second.

Address Resolution Protocol

Address Resolution Protocol provides dynamic mapping of network addresses, such as IP addresses, to corresponding hardware addresses, such as MAC addresses.

ARP

adjoint analysis

Adjoint analysis is the detection mechanism that detects unknown objects that is active in the same time period or with the same behavior pattern of the target object. The purpose is to detect the criminal partner.

administrator

The most advanced user who has the highest administration permissions to systems or businesses.

administrator right

A user with the privilege of unrestricted access to a system, including the ability to create, edit, or delete any folders or files and change system settings.

aggregate function

A function where the values of multiple rows are grouped together to form a single value of more significant meaning or measurement such as a set, a bag, or a list.

Alibaba Cloud

Alibaba Cloud, the cloud computing brand of Alibaba Group. The world-class outstanding provider of cloud computing technology and services. Established in 2009 with multiple R&D research centers and operation institutions in Hangzhou, Beijing, and Silicon Valley.

Alibaba Cloud engine

Alibaba Cloud engine is the web-based managed environment based on cloud computing infrastructure. It simplifies the building and operations of web-based applications with scalability function of application load balancing.

Alibaba Cloud platform

You are in charge of the integrity and confidentiality of the data, token, password related to your Alibaba Cloud products and services managed and trusted by Alibaba Cloud platform.

Ali-Tomcat

A container that Enterprise Distributed Application Service (EDAS) depends on to run services. It integrates a series of core functions, such as the release, subscription, and call chain tracking of services. Applications must be released in this container whether in the development environment or the runtime environment.

AnalyticDB for PostgreSQL

- AnalyticDB for PostgreSQL is a data warehousing service that provides online Massively Parallel Processing (MPP). AnalyticDB for PostgreSQL is developed based on the Greenplum Open Source Database program and is enhanced with some in-depth extensions by Alibaba Cloud. It supports features including the OSS external table, JSON data type, and HyperLogLog estimation analysis. AnalyticDB for PostgreSQL provides flexible hybrid analysis functions through query and anticipation of SQL2008 standard and OLAP analytic and aggregate function; it also supports the hybrid storage of row storage and column storage, data

compression technology to reduce the storage cost. AnalyticDB for PostgreSQL provides online scalability, backup, performance monitoring, and other services. Users do not have to manage complicated large-scale MPP clusters. AnalyticDB for PostgreSQL allows DBA, developers, and data analysts to focus on how to enhance productivity through SQL and create enterprise core values.

- AnalyticDB for PostgreSQL is one of the most advanced open-source database. As the ancestor of the academic relational database management system, AnalyticDB for PostgreSQL features by the complete implementation of the SQL rules and abundant support of data types , including JSON data, IP data, and geometric data. Most of these supported data types are not supported by most other commercial database. Except for functions like complete support of tasks, sub queries, multi-version control, data integrity check, AnalyticDB for PostgreSQL is integrated with key features like high availability and backup/restore to reduce the operation pressure. Current AnalyticDB for PostgreSQL also supports version 9.4.

anti-leech

A function used to block leech access of requests from other websites. Web Application Firewall (WAF) controls access based on the source URL. WAF checks the request for resources such as images or files from a client. If WAF detects that the request is from another website, WAF blocks the request. The use of anti-leech minimizes bandwidths consumed by leech requests to improve performance.

API reference

Besides widely known as the Application Programming Interface, API also refers to the documentation of an API, or a help document that provides instructions of request parameters and request samples for developers to quickly understand and use it.

application

An application program that is created using an image or an orchestration template. Each application can contain one or more services.

application diagnosis

Enterprise Distributed Application Service (EDAS) provides the detailed troubleshooting and performance analysis for applications, including the statistics and method tracking of the JVM heap/non-heap memory, class loader, thread, and Tomcat connector on the single machine where the application is running.

application grouping

An in-application group management function that groups all the Elastic Compute Service (ECS) instances of an application to deploy the ECS instances in different groups with packages of different versions. It allows you to implement Operations & Maintenance (O&M) methods such as beta release, AB test, and Gated Launch, and supports you to manage application lifecycle, monitor resources, and send alarm notifications from the perspective of grouping, which improves the O&M efficiency rapidly.

application hosting environment

The physical environment where application hosting services are offered from. Traditionally, organizations must build and maintain infrastructures to run applications locally. However, with software as a service (SaaS) model, businesses can use online hosted applications that enable them to reduce costs by paying by usage, enjoy seamless, easy upgrades, and easily integrate with other existing data and systems.

application migration to the cloud

The action of monitoring the real-time traffic and historical information of the application, which allows you to monitor the health status of the application and quickly detect and locate the issues.

application monitoring

The action of monitoring the real-time traffic and historical information of the application, which allows you to monitor the health status of the application and quickly detect and locate the issues.

application runtime environment

The runtime environment of applications, that is, the Enterprise Distributed Application Service (EDAS) container, including HSF and Pandora.

Apsara

A hyper-scale and universal computing operating system that is independently developed by Alibaba Cloud and provides services for the world. It can connect millions of servers all around the world to form a supercomputer and provide computing capabilities for the community in the form of online public services. From the PC-based Internet to the mobile Internet and Internet of Everything, the Internet has become a new infrastructure in the world. Apsara intends to resolve the scaling, efficiency, and security problems in human computation. Apsara revolutionizes the three aspects of cloud computing to provide powerful, universal, and beneficial computing capabilities to everyone.

Apsara Distributed File System

Apsara Distributed File System is the file system component in the Apsara system. It connects the disks of the PC servers with no high availability as a whole to provide file storage capacity with stable and secure access.

Apsara File Storage NAS

A distributed file system that provides file storage services for compute nodes such as Apsara Stack ECS instances, E-HPC, and Docker. Apsara File Storage NAS provides a standard file access protocol and allows multiple users to access files. Apsara File Storage NAS features unlimited capacity and scalable performance, a single namespace, high reliability, and high availability. You can use all these features without the need to modify your existing applications.

Apsara Infrastructure Management Framework

Apsara Infrastructure Management Framework is a set of automatic management system for data centers, hardware lifecycle of management data centers, and various static resources (such as program, configuration, system image, and data). Apsara Infrastructure Management Framework provides a set of solutions such as version control, deployment, and hot upgrade for Apsara products and other Alibaba applications, which improves the automatic operation effects in the large-scale environment. It enhances the operation efficiency and system availability.

Apsara Name Service and Distributed Lock Synchronization System

The distributed coordination service (Apsara Name Service and Distributed Lock Synchronization System), similar to Paxos protocol, consists of multiple servers and similar file system to store data, provides user request capacity for users in need of high availability and high concurrency. As one of the significant basic components, it provides services related to distribution and consistency in the Apsara system. Compared to traditional products of the same kind, it allows high performance and supports horizontal expansion. The field counterparts are many, such as Zookeeper.

Apsara Stack

A proprietary, dedicated enterprise cloud platform that allows enterprises to improve utilization of their existing on-premises data center as well as install innovative services in security, and meet requirements in data sovereignty and compliance.

Apsara Stack Security

An end-to-end security service established based on the data analysis capability of Alibaba Cloud's cloud computing platform. It provides security vulnerability detection and web page Trojan detection for small to medium-sized websites. It also provides host intrusion detection and anti-DDoS for cloud server users.

ApsaraDB for MongoDB

The cluster version of ApsaraDB for MongoDB. You can purchase multiple mongos and shard nodes, and combine them with a single ConfigServer to form a cluster version of ApsaraDB for MongoDB. This makes it easy to create the distributed database system for ApsaraDB for MongoDB.

ApsaraDB for RDS

A stable, reliable, and elastically scalable online database service. Based on Apsara distributed system and high-performance storage, ApsaraDB for RDS supports the MySQL engine. It provides a complete set of solutions for disaster recovery, backup, recovery, monitoring, and migration to free you from worries about database O&M.

RDS

atomicity

Where transactions are an indivisible and irreducible series of database operations so that either all operations occur, or none occur. A guarantee of atomicity prevents updates to the database occurring only partially, which can cause greater problems than rejecting the whole series outright.

attribute

- The characteristics of object relations. For Graph Analytics, attributes belong to relation or entity, and can not exist alone. For instance, human being attributes such as height, weight, place of birth, and name; mobile phone attributes such as home location, operator. The main key is also one attribute, in the same way that ID is one of the human attributes, and mobile number is one of the mobile phone attributes.
- Data of the row where properties reside. No limit for the number of property columns in each row.

Aurora

The HA (high-availability) management system of ApsaraDB for RDS. It checks the status of the master database every three seconds. When it detects that the master database is down, it switches the SQL requests of users to the slave database quickly.

authentication

A group of processes where the confidence for user identities is established and presented via electronic methods to an information system.

authoritative DNS resolution

A service that resolves root domain names, top-level domain names, and domain names of other levels.

authority domain

Authority domain is the domain name that local DNS server resolves. The domain resolution data configuration and management is done in local DNS server.

authorization

A process in which permissions required to perform a certain job are granted to the related personnel. It is the key to organization operations.

authorized object

An attribute of the privilege group rule. In a VPC, it can be a separate IP address or network segment. In a classic network, it can only be a separate IP address (the intranet IP address of an ECS instance).

Auto Scaling

- A service used to automatically adjust the elastic computing resources according to your business requirements and policies. It can automatically increase the Elastic Compute Service (ECS) instances when the business grows, and automatically decrease the ECS instances when the business declines.
- A function of detecting the resource (CPU, RT, and load) status of each server in the cluster and scaling in or out the cluster in real time based on the status to guarantee the quality of service and improve the availability of the cluster system.

automatic snapshot policy

A rule that defines when the automatic snapshots are taken and how long they are retained.

B

backbone analysis

Backbone analysis is specific to group network. It adopts intelligent business algorithm to detect the core backbone node for relation network.

back-end server

A set of cloud servers that accept load-balanced distribution requests. Server Load Balancer forwards access requests to this set of servers based on the rules you set.

back-to-origin error

An error that occurs when the source site fails to respond to the request forwarded by Alibaba Cloud Anti-DDoS Pro because the IP address of the source site is blacklisted by the firewall.

backup

The process of backing up, refers to the copying into an archive file of computer data that is already in secondary storage, so that it may be used to restore the original after a data loss event. The backup has two distinct purposes. The primary purpose is to recover data after its loss, be it by data deletion or corruption. The secondary purpose of backups is to recover data from an earlier time, according to a user-defined data retention policy, typically configured within a backup application for how long copies of data are required. Since a backup system contains at least one copy of all data considered worth saving, the data storage requirements can be significant. Organizing this storage space and managing the backup process can be a complicated undertaking. A data repository model may be used to provide structure to the storage. Nowadays, there are many different types of data storage devices that are useful for making backups. There are also many different ways in which these devices can be arranged to provide geographic redundancy, data security, and portability.

backup system

The backup system takes charge of store a second copy of ally the database instance in the cluster, and store them in an integrated place.

basic cloud disk

Disks installed on the cloud server to support low I/O loads. It provides Elastic Compute Service (ECS) instances with the I/O performance of hundreds of IOPS.

basic monitoring

The action by which EDAS collects data from ECS instances that are running a specified application, and then monitors the CPU, memory, load, network, and disks used for system analysis and data processing.

bastion host

A host implemented based on the forward proxy protocol. It records data streams of typical O&M protocols, such as the Secure Shell (SSH) , Remote Desktop Protocol (RDP) for Windows, and SSH (or Secure) File Transfer Protocol (SFTP). Then, it reassembles the data for O&M and auditing.

behavior analysis

A method that displays time-based distribution frequency of an event.

BI report

The smart commercial suite for big data. It provides massive online data analysis through drag-drop operations and abundant visual effects meanwhile helps users with data analysis and detection effortlessly.

billing account

An account used to purchase Enterprise Distributed Application Service (EDAS) products. One billing account can be bound to at most five primary accounts, and the billing account is also a primary account.

binary log file position

A method used in MySQL binary log files. Each line records a data change action. The position of the line is called the binary log (binlog) file position.

blank dispatch

Blank dispatch is generated during data scheduling, does not execute task script, and only get started in defined time period. It is successful by default.

block storage

A low-latency, persistent, high-reliability, and random block-level data storage provided for Elastic Compute Service (ECS) by Alibaba Cloud. It supports automatically copying your data in a zone, which avoids data unavailability caused by unexpected hardware faults and protects

your business against the risk of component faults. Similar to a disk, you can format, create a file system, and persistently store the data on the block storage mounted to an ECS instance.

blood analysis

Blood analysis displays the blood relation between people according to the household number.

bridging

A computer networking device that creates a single aggregate network from multiple communication networks or network segments. This function is called network bridging. In the OSI model, bridging is performed in the data link layer (layer 2). If one or more segments of the bridged network are wireless, the device is known as a wireless bridge.

broadcast

The action of transmitting a packet that will be received by every device on the network.

broadcast table

These tables do not divide any data across data partitions. Each data partition has a copy of the data. Updates to the data are delivered to all partitions. It is usually only used for small data and must be included in the join table.

brute force password cracking

A type of attack used by attackers who keep trying to crack the password by continuously specifying the password ranges based on the password naming rules until all verifications are completed.

bucket

A unit that is used to manage stored objects. Objects must belong to a specific bucket.

buffer pool

A cache of existing database connections. It allows applications to reuse database connections that already exist in the pool, and reduces repeated attempts to create new database connections. This technology can improve system performance and avoid the overhead of building a new connection.

Business Foundation System

Business Foundation System is the logic layer of the Alibaba Cloud product. It maintains the relation between cloud product instance and users, the relation between instances and logic cloud concept such as region/zone, buffer of the front-end request and mitigates the back-end pressure.

byte hit rate

The probability that a requested number of bytes hits the cache within a specified period.

C

canonicalized query string

A query string that has been converted into a "standard", "normal", or canonical form by concatenating the (=) sign with the ampersand sign (&) and parameter names in lexicographic order.

capacity bottleneck

Capacity bottleneck refers to the service barrier as the data volume and visit counts to the standalone database increases.

capacity instance

A cost-friendly instance type designed for storage as well as read and write.

capacity planning

A complicated and continuous performance study on resource consumption of softwares and hardware in an existing system. Performance stress testing becomes a daily routine. Users in charge of applications can easily view application performance metrics and perform precise capacity planning for applications based on those metrics and the current system operating water level.

certificate

Certificates are used in HTTPS. After uploading a certificate to a Server Load Balancer, users can bind the certificate during HTTPS listener creation to provide HTTPS service. Certificates include both server-side and client-side certificates.

character encoding

Computing actions that represent a repertoire of characters by some kind of encoding system.

Depending on the abstraction level and context, corresponding code points and the resulting code

space may be regarded as bit patterns, octets, natural numbers, and electrical pulses. ASCII is an example.

checkpoint

Consumer stores the shard expenses that are assigned for them to service end. When the shard is assigned to other consumers, the shard consumption point can be obtained. The next consumer starts consumption from that point.

classic network

The Alibaba Cloud products of classic network are centrally deployed in the Alibaba Cloud infrastructure network. Alibaba Cloud plans and manages the network and is more suitable for customers that require more network feasibility.

classified protection (of information security)

An important aspect of information security and risk management is recognizing the value of information and defining appropriate procedures and protection requirements for the information. Apsara Stack service provides security protection to the customer information system through international and domestic certification of trusted cloud, classified protection, management system of information security, and cloud security.

Classless Inter-Domain Routing

A method used to assign IP addresses to users and efficiently route IP packets on the Internet to classify the IP addresses.

CIDR

client

A program that establishes connections to send requests.

cloud compute

The mode that supplies and manages the shared physical and virtual resources in a self-help method through the network.

cloud computing ecosphere

The cloud computing ecosphere builds the cloud computing ecosphere for partners to create synergy.

cloud disk

An independent disk that can be mounted to any Elastic Compute Service (ECS) instance in the same region and zone. It can be classified into three types based on the performance: Ultra cloud disks, SSD cloud disks, and basic cloud disks.

cloud instance

Cloud instances share one set of management system in the cloud platform. Generally speaking a cloud instance is divided into multiple regions according to its geographic site. One region is consisted of multiple AZones. In Apsara Stack one AZone physically corresponds one on-premises data center.

cloud security

Cloud security is the overall concept of hardware, user, institution, and secure cloud platform based on the commercial mode of cloud computing application.

CloudMonitor

A centralized monitoring platform for Alibaba operation engineers and developers, which monitors the devices, networks, databases, application clusters, and core services of Alibaba Group.

cluster

- A collection of cloud resources required to run containers. It is associated with several server nodes, SLB instances, VPC instances, and other cloud resources.
- A logical group of hosts. Hosts that are deployed in a cluster must have the same OS (VM monitor: Hypervisor) installed, and can share the same layer-2 network connection and access the same primary storage. In data centers, a cluster typically corresponds to a rack.
- The ApsaraDB for MongoDB supports cluster versions. Users buy multiple Mongos, multiple shards, and one configuration server to build the cluster version, and easily obtain one distributed MongoDB database system.

command line

A command that runs in DOS.

common analysis

Common analysis is to search for the object across multiple space and time periods. The applied scenario is to search for the accomplice for certain case. It supports co-occurrence analysis in round, rectangular, and polygon shapes.

common neighbour analysis

An analysis on common contacts of a group of objects of the same type or different types.

compute node

A feature that allows you to compile and run Spark, Spark SQL, and Hive SQL tasks directly on the E-MapReduce console.

configuration push

A configuration management feature provided by Enterprise Distributed Application Service (EDAS), which allows you to centrally manage the configurations of distributed systems in the EDAS console, add, modify, and delete configurations in real time, and push the configuration updates globally or within the application.

connection mode

A mode that defines the transmission path of data packages for ApsaraDB RDS instances. Performance is the standard connection mode. Safety is the high security connection mode.

console

A graphical user interface for products that lets you perform common operations.

consumer

Each consumer is assigned with several shards and must consume the shard data. The consumer name in the same consumer group is unique.

consumer group

A sub-resource of Logstore. Consumers with the same consumer group name consume data of the same Logstore, but the data consumed by each consumer is different. Up to five consumer groups can be created under one Logstore, and the group names must be unique within the Logstore. Different consumer groups under the same Logstore consume data independently.

container

A runtime instance created from Docker. A node can run multiple containers.

container clinic

Also known as container monitoring. It provides various monitoring metrics for Tomcat containers.

Container Service

A high-performance and scalable container management service. It enables you to manage the lifecycle of containerized applications with Docker and Kubernetes. Container Service provides multiple application release methods and the continuous delivery capability. It supports microservice architectures. Container Service is an ideal cloud running environment for containers. It simplifies the setup of container clusters and integrates it with the capabilities of Alibaba Cloud such as virtualization, storage, network, and security.

content moderation

Based on in-depth learning technology and massive data accumulated by Alibaba over the years, Content Security provides photo, video, texts, and other multi-media content for intelligent recognition service. It helps user mitigate the default risk of porn, violence, politics, advertisement, abuse, and other negative user experience, and cuts down the massive manual check cost.

cookie

Data (usually encrypted) that websites store on your local terminal for identity identification and session tracking.

cool-down time

A period of locking time after a scaling operation in a scaling group. During the locking time, you cannot perform a scaling operation on the same scaling group.

cooperation & share

Cooperation & share is a new analysis mode provided by Graph Analytics product. It shares the one analysis result with others, pass on the thoughts and experience to other users, and combine the wisdom and experience of other users together to form the multi-operation, or group operation to propel the overall improvements. This will integrated the team members as one.

CPU usage

The amount of time for which a central processing unit (CPU) uses to process instructions of a computer program or operating system.

creating

The running status of a software or system. It indicates the software or system is being created.

cross-site scripting

A type of computer security vulnerability typically found in web applications. XSS enables attackers to inject client-side scripts into web pages viewed by other users. A cross-site scripting vulnerability may be used by attackers to bypass access controls such as the same-origin policy

xss

CU

CU describes the minimum operation ability for a single stream task, that is the event process ability with limited CPU, storage, and I/O.

custom image

Created by using snapshots. The created image can be used to create an Elastic Compute Service (ECS) instance.

cyber storm

A situation where messages broadcast on a network cause multiple hosts to respond simultaneously, and this consumes enough network resources to prevent normal traffic on the network.

D

dashboard

A visual that allows users to quickly and easily monitor data models and other details in an intuitive manner.

data application layer

An abstraction layer that defines and generates personalized and diversified data metrics applicable to multiple business requirement scenarios.

data center

A large group of resources (including regions and zones) used by Alibaba Cloud.

data cleansing

A disk (hard disk) that is installed on the device board where other disks are located. Do not insert, remove, or move the disk without permission. Generally, the disk includes the partition where the computer operating system resides and other partitions.

data common layer

Abstract common subject based on business data, with the common standard, specification, and can be shared. It is the bridge between infrastructure and application layer. Also known as common data center.

data compression

A technique that uses algorithms to reorganize data, reduce redundant data, and save storage space without loss of valid data. It can improve the data transmission, storage, and processing efficiency.

data consumed timestamp

A timestamp that records the last time subscription data was consumed by the downstream SDK. The SDK sends an ACK packet to the DTS server for each piece of consumed data. The DTS server updates and saves the respective timestamp. When the SDK restarts unexpectedly, the DTS server automatically pushes subscription data based on the latest timestamp.

data development

The development process of stream computation (the process to draft BlinkSQL), which is defined as data process.

data disk

A disk that contains only data, excluding the operating system.

data disk mounting

In Windows server system user accesses the disk data through SATA or SAS interface. In Linux system, the disk data is not available for direct access. It requires to perform mounting action to access the data.

data introduction

Data introduction migrates data from one system to another system in batch. The migrated data includes structure, data, and definition.

Data Management

A service that integrates a wide range of capabilities, such as data management, object management, resource inventorying, instance authorizations, security audits, data trends, data tracking, data graphs, performance and optimization, and server management. DMS can be

used to manage NoSQL databases and relational databases such as MySQL, SQL Server, PostgreSQL, MongoDB, and Redis. It can also be used to manage Linux servers.

DMS

data mid-end

A framework and model of data construction, management, and application. It shields the complexity of business systems in the underlying hardware, processes and outputs standard, diversified, and converged data, and provides a variety of convenient data applications to support different business scenarios in the upper layer and drive business intelligence by using intelligent data.

data migration to the cloud

Migration of data from traditional architectures to the cloud.

data owner

The person in charge of a database or a table. They are responsible for the management and control of other users who use the database or table.

data persistence

A method to convert data between data models in the memory and storage models.

data protection

Data protection can be categorized by technology. The technologies involve two aspects: the mechanism and the components or entities to be executed. The mechanism describes how to implement protection and where to execute components. The mechanism is divided into external data protection, data transformation, and internal data protection based on the technologies it depends on.

data replication center

The infrastructure for real-time synchronization of the heterogeneous database.

data replication system for MySQL

Data Replication System for MySQL refers to the middleware for Alibaba Cloud database synchronization. Through the MetaQ message it senses the change of database binlog and replicates the database.

data scope

The scope of the time stamp for the incremental data stored in the prescription channel. The time stamp of the incremental data corresponds to the time stamp when the piece of incremental data is applied and recorded by event log in the ApsaraDB for RDS instance. By default the prescription channel only stores the incremental data of one day. The data transmission service cleans the incremental data regularly, and update the data scope of prescription channel.

data sharding

The means of database partitioning that separates very large databases into smaller, more easily manageable parts called data shards.

Data Silos

Data Silos refers to the independent data storage system that cannot be connected for computing.

data source

The original data storage from each business database. It is the basic source of data construction, also known as vertical data center.

data traffic

The amount of data moving across a network at a given point of time. Traffic in computer networks is mostly data encapsulated in network packets, which provide the load in the network.

Data Transmission Service

A service that helps migrate data between different data sources such as relational databases, NoSQL, and OLAP. DTS integrates data migration, data subscription, and real-time data synchronization. It provides millisecond-level long-distance asynchronous data transmission in public cloud and hybrid cloud scenarios. Its underlying data stream uses the remote active-active infrastructure used for Double 11. The infrastructure has provided stable real-time data streaming for thousands of downstream applications for three years. You can use DTS to easily create secure, scalable, and highly available data architecture.

DTS

data update

A type of database update. Data updates only modify data. They do not modify the schema.

data warehouse

An efficient and secure environment for offline data development (formerly Data IDE) with powerful open APIs, to create an ecosystem for redevelopment. It provides visual development interfaces and functions such as offline job scheduling, offline job operations and management, rapid data integration, and multi-person collaboration.

DataWorks

An efficient and secure environment for offline data development (formerly Data IDE) with powerful open APIs, to create an ecosystem for redevelopment. It provides visual development interfaces and functions such as offline job scheduling, offline job operations and management, rapid data integration, and multi-person collaboration.

database

The database instance of KVStore for Redis. It supports 256 instances of database and the data is firstly written to the DB 0 by default.

database engine

The core service used to store, process, and protect data. It provides controlled access and rapid transaction processing to meet the requirements of enterprise applications that process massive data. It can be used to create relational databases that process transactions and data analysis online. This includes the creation of tables that store data and database objects that are used to view, manage, and guarantee data security (such as indexes, views, and storage procedures).

dataset dimension

The key value that is used to aggregate a dataset when it is created. It is similar to the GroupBy column.

dataset indicator

A Solid-State Disk (SSD) that is installed on the device board where other disks are located. Unlike the basic cloud disk, data is not triplicated but the Redundant Array of Independent Disks (RAID) technology is used. Therefore, you cannot avoid the data loss if a single physical machine is down.

debugger

A computer program or tool that is used to debug other programs. The code to be examined can be alternatively run on an instruction set simulator (ISS) to check the running status and

troubleshoot errors. This technology is useful when development is bottlenecked or problems cannot be located.

decoupling

A process that converts mathematical equations with multiple variables to an equation group with a single variable. This simplifies analytic calculation as the result of the equation is not directly affected by multiple variables. A multi-variable system can be converted to multiple independent single-variable systems by controlled variable selection and coordinate transformation, which means decoupling variables.

deep learning

A branch of machine learning. It is an algorithm that attempts to use multiple processing layers with complex structures or composed of multiple nonlinear transformations for high-level abstraction of data.

default forward

DoS Attack is such event that forwards the authority domain resolution that should be handled by non-local DNS server to another DNS server for resolution.

Denial of Service (DoS) attack

A type of attack in which the perpetrator seeks to make a machine or network resource unavailable to its intended users by flooding the targeted machine or resource with superfluous requests.

deployment

An update operation on Kubernetes clusters. Deployment is more widely applied than ReplicaSets (RSs). You can use the deployment to create a service, update a service, or perform a rolling update for a service. A new RS is created when you perform a rolling update for a service. The number of replicas in the new RS increases to the ideal status while the number of replicas in the original RS decreases to zero, which constitutes a compound operation. In this scenario, deployment is more suitable than an RS to describe the compound operation. We recommend that you do not manage the RS created by the deployment.

deployment set

Capabilities provided by Elastic Compute Service (ECS) that allow you to detect the physical topology of the host, rack, and switch and select a deployment policy that meets the business

requirements according to your business type to improve the overall reliability or performance of your business.

Destination Network Address Translation

The action of translating the destination address of an IP packet to another address.

DNAT

developer

The resource consumer and data constructor in a project, who can edit and delete resource objects from a project.

Diamond

The distributed configuration center. It provides real-time posting service.

digital city

The transformation of cities and urban areas through the use of modern technologies to provide novel and interactive city-wide services for governments, citizens, and business. It may also be referred to as a 'smart city'.

disk array

A data storage system designed to clear off the Single Points Of Failure (SPOF). Disk array components are generally hot-swappable.

dispatch period

Dispatch period is the time interval generated by data scheduling.

dispatch timing

Dispatch timing is the startup time required by data scheduling.

distributed

A mode in which different services are distributed on different areas and devices, and each node performs a specific task.

Distributed Denial of Service

A cyber-attack that an attacker sends a large number of valid requests to make the network become unavailable by consuming huge network resources. The attack can be divided into the following types: Attacks that interrupt or even block normal network communication by overloading

the network. Attacks that overload servers by submitting massive requests to the servers. Attacks that prevent an authorized user from accessing a server. Attacks that prevent a service from communicating with a specific system or individual.

DDoS

Distributed Denial of Service (DDoS) attack

A type of DoS attack in which an attacker makes a target network unavailable by overwhelming it with valid requests from multiple sources. Types of DDoS attacks are listed as follows: attacks that interrupt or even prevent normal network communications by overloading networks; attacks that overload servers by sending a large number of requests to the servers; attacks that prevent an authorized user from accessing a server; attacks that prevent a service from communicating with a specific system or user.

Distributed File System

A client/server-based application that allows clients to access and process data stored on the server as if it were on their own computer. When a user accesses a file on the server, the server sends the user a copy of the file, which is cached on the user's computer while the data is being processed and is then returned to the server.

distributed index

The use of a distributed indexing algorithm to construct indexes that are partitioned across several machines.

distributed SQL engine

Distribute the data to multiple data nodes (different database and different tables) according to data condition. Optimize the data SQL operation distribution, and get optimized execution efficiency.

Distributed System Performance Monitor

Distributed System Performance Monitor is the system component to collect, monitor, and diagnose information. It deploys light-weighted information collection model on each physical machine to obtain the performance, operation status of the operating system and application software and monitors the cluster fault. Through the analysis of the Apsara operation status it evaluates the overall system.

distribution key

A distribution key is a column (or group of columns) that is used to determine the database partition in which a particular row of data is stored.

docker image

A standard packaging format of a containerized application in Docker. You can specify an image to deploy containerized applications. The image can be from Docker Hub, Alibaba Cloud Container Hub, or your registry. An image ID is uniquely identified by the URI of the image repository and the image tag (latest by default).

domain name

The name of a computer or a computer group on the Internet. It consists of several parts separated by periods (.) to identify the electronic location of the computer or computer group for data transfer.

domain name resolution

A function of mapping a domain name to a corresponding IP address based on DNS.

down

The scenario that operation system cannot recover from a serious systematic mistake, with prolonged system response, therefore, the system has to be restarted.

downstream traffic

The number of bytes that are downloaded from the Internet.

Dubbo

A high-performance, Java based RPC framework open-sourced by Alibaba. It is the core framework of Alibaba SOA and is widely used across all Alibaba web platforms.

E

EagleEye

An Enterprise Distributed Application Service (EDAS) service monitoring system, which tracks and analyzes the system calls, message sending, and database access information of the distributed system to precisely identify the bottlenecks and risks of the system.

ECS Bare Metal Instance

A new computing server product that combines the elasticity of virtual machines and the performance and features of physical machines, which is built based on the next-generation virtualization technology that is independently developed by Alibaba Cloud.

ECS Operations and Maintenance System

The operations and maintenance system of ECS.

ECS Server Controller

Resource scheduling system of ECS.

ECS/VPC Deployment System

The deployment tool for ECS and VPC.

EDAS agent

A Daemon installed on ECS instances. It is responsible for communication between the EDAS service cluster and any applications deployed on the ECS instance, and enables application-based controls.

EDAS application lifecycle

EDAS application lifecycle is the basic unit of EDAS management. One application contains multiple machines. EDAS provides management mechanism for complete life cycle, and can complete the full application management from publish to operation, including creation, deployment, startup, rollback, scaling, and stop offline operation.

EDAS RPC service

EDAS RPC service provides support to Dubbo framework. Applications that are developed by Dubbo framework and are deployed with WAR method can publish and manage applications seamlessly in EDAS platform. Functions such as service management and data operation are also provided by EDAS.

Elastic Compute Service

A simple and efficient cloud computing service that features elastic processing capabilities. It supports many operating systems, such as Linux and Windows.

ECS

Elastic Network Interface

Also known as secondary ENI. You can create a secondary ENI and attach/detach it to/from an instance. The ENI created by default when the Virtual Private Cloud (VPC) instance is created is a primary ENI. The lifecycle of the primary ENI is the same as that of the instance. You cannot detach the primary ENI from the instance.

ENI

E-MapReduce

A service that is built on Apsara Stack ECS instances. It uses resources from open-source big data ecosystems such as Hadoop, Spark, and HBase to provide an end-to-end big data processing and analysis service. You can use E-MapReduce to manage your clusters, jobs, and data.

E-MapReduce job

A basic business unit for implementing a specific big data processing and analysis service.

endpoint

- The access domain name served by the OSS over the Internet or intranet.
- The connection URL that corresponds to an instance. You must specify an endpoint before you can perform any operations on tables and data.

Enterprise Distributed Application Service

A core product of Alibaba's enterprise-level Internet framework solutions. EDAS uses the tested and proven distributed products of the Alibaba middleware team as its core components and provides high-availability distributed solutions for the enterprise-level cloud computing market. By making full use of Alibaba Cloud's resource management and service systems and introducing the whole set of mature distributed products of Alibaba Cloud middleware, EDAS helps enterprise-level customers build large-scale distributed application service systems easily.

EDAS

error code

In order to locate the issue, establish the association between error type and error code. When error occurred in either hardware or software, report to administrator by display of error code. Administrator locates the specific reason that lead to the software or hardware fault.

eviction policy

A policy used to eject infrequently used data. It is consistent with Redis eviction policy behaviors.

exclusive virtual host

Exclusive virtual host is the complete server resource with no fight for the resource, which makes it more stable, with no limit of traffic, which make it more speedy, with independent IP, which makes it easier to promote. It suits more for the enterprise website project.

existing data synchronization

Initialization of the historical data of the synchronization object to the target instance before the link incremental data is synchronized.

expansion partition

Expansion partition is achieved through split. When splitting, the ShardID in read/write status and one MD5 are required. The MD5 must be larger than the inclusiveBeginKey and less than the exclusiveEndKey.

extension analysis/associated query

Extension analysis/associated query implements unlimited relation analysis for single or a batch of objects. Associated query helps realize the unlimited association of informations. The key of intelligence analysis work is to detect critical part of leads and significant information from massive, unassociated pool of information, that is to transform the information into operable intelligence process. The associated query provides two methods: simple and advanced.

F

FatJar

A new computing server product that combines the elasticity of virtual machines and the performance and features of physical machines, which is built based on the next-generation virtualization technology that is independently developed by Alibaba Cloud.

firewall

A network security system used to separate intranets from public networks. It monitors and controls incoming and outgoing network traffic based on predetermined security rules.

forward compatibility

A design characteristic that allows earlier versions to support data generated by later versions.

forwarded domain name

A domain name that is resolved by the local DNS server. Domain name resolved data is configured and managed on the local DNS server. The local DNS server forwards domain name resolution results to another DNS server for further resolution.

forwarding weight

The weight for traffic forwarding that you can specify for each Elastic Compute Service (ECS) instance in the back-end server pool according to the external service capabilities and situations of the back-end ECS instance. The higher the weight is, the more access requests are assigned to the ECS instance.

FPGA cloud server

FPGA cloud server provides computing instance with FPGA function. Based on Alibaba elastic computing framework, user can create FPGA instance within minutes, and create self defined hardware accelerator.

fragmented storage

Splits files into multiple fragments and multiple copies across multiple storage disks.

FreeBSD image

An Elastic Compute Service (ECS) instance environment based on the FreeBSD operating system. Currently, the supported versions include 10.1 (64 bit).

full backup

The process of backing up all data or applications at a time point.

full data migration

A type of migration task. It refers to the migration of all data except Data Definition Language (DDL) from the source instance database to the target instance. If you select only full data migration but not incremental data migration when you create a migration task, the data newly added to the source instance will not be migrated to the target instance during the migration process.

full migration

A mode of data migration. Within the specified period, all data is migrated from the source system to the target system in a way data consistency is guaranteed.

full snapshot

The first created snapshot of a disk that saves all the disk data.

G

geo-bubble chart

A style of rendering where circles are positioned on specified locations on a geo-chart with defined colors and sizes.

geo-chart

A map of a country, a continent, or a region with areas identified according to specified data.

geo-disaster recovery

Disaster recovery involves a set of policies, tools and procedures to enable the recovery or continuation of vital technology infrastructure and systems following a natural or human-induced disaster. A remote disaster recovery location produces backups on a regular basis. Backups can be made to an on-premise, internal backup server, or to a cloud based service.

GetHistograms

A method used to query the number of logs that meet the query condition, and the distribution of these logs in the queried time range (namely, the number of logs that meet the query condition in each sub time range), without returning the specific raw logs.

GetLogs

A method used to query logs that meet the query condition, with all raw logs returned.

glitch

A short-lived fault in a system, such as a transient fault that corrects itself, making it difficult to troubleshoot.

GPU cloud server

GPU cloud server is based on the computing service of GPU application. It is used in application scenarios such as video resolution, graphics rendering, deep learning, and scientific computing. This product features by realtime high speed computation with floating point computing ability.

graceful service degradation

A downstream process in which low priority calls to non-core service providers are timed out to guarantee that upstream core applications are not affected.

group analysis

A method that analyzes the relationships among objects of the same type or different types. The relationships include direct and indirect relationships.

group ID

Identifies logically shared nodes that represent classes of devices with identical functions.

guest

A participant of a project who can view resource objects of a project, but cannot edit or delete them.

H

hash

Function that can be used to map data of arbitrary size onto data of a fixed size. The values returned by a hash function are called hash values, hash codes, digests, or simply hashes. Hash functions are often used in combination with a hash table, a common data structure used in computer software for rapid data lookup. Hash functions accelerate table or database lookup by detecting duplicated records in a large file.

health check

A basic function of Server Load Balancer, which is used to check the business availability of the back-end servers (Elastic Compute Service (ECS) instances), improve the overall availability of the front-end business, and avoid the effect on the overall services caused by the abnormal back-end ECS instances.

heartbeat

A periodic signal generated to indicate normal operations. It is usually sent between machines at regular intervals.

High Availability

A characteristic of system and application durability in which downtime for users due to regular maintenance operations (planned) and sudden system crashes (unplanned) is minimized. A highly available system is likely to operate continuously without failure for a desirably long time.

HA

high concurrency

A factor that must be considered in the distributed system architecture design of Internet. It uses a method to make sure that the system can handle large numbers of requests concurrently.

high-availability control system

Responsible for monitoring system health and real-time handovers between all database instances to ensure high availability (up to 99.99%).

High-Availability Virtual IP Address (HAVIP)

An intranet IP resource that can be created and released independently. You can use the ARP protocol on the Elastic Compute Service (ECS) instances to declare the IP.

HAVIP

highly available cluster

A server cluster technology that reduces service interruptions. It protects your business programs to provide uninterrupted services and minimizes the impact caused by softwares, hardware, or human errors.

high-performance cluster instance

A collection of high performance instances that can connect to a single database.

high-performance instance

High-performance instance is the instance with high read/write performance.

High-performance Service Framework

A distributed service framework for enterprise Internet architectures. It is based on a high-performance network communication framework and provides various proven features such as publication, registration, call, routing, authentication, rate limiting and throttling, degradation, and call chain tracking of services.

HSF

High-Speed Service Framework

A distributed service framework for enterprise. It is based on a high-performance network communication framework and provides service registration, publication, invocation, routing, and other related features.

host intrusion detection

Apsara Stack Security performs security analysis on the host log records, and detects and reports aggressive behavior in real time, such as system password cracking and logons from abnormal IP addresses.

host intrusion prevent system

A method that Alibaba Cloud Security uses to perform security analysis on the host logs, detect and report the aggressive behaviors in real time, such as system password cracking and logons from abnormal IP addresses.

HyperText Transfer Protocol

A universal, stateless, and application-oriented protocol for distributed, collaborative, and hypermedia information systems.

HTTP

I

Idempotence

It describes an operation that produces the same results no matter how many times a client makes it. Note that while idempotent operations produce the same result on the server (no side effects), the response itself may not be the same (for example, a resource's state may change between requests).

identity credential

Authentication you must provide when you log on to a user account. For example, a password, AccessKey, or an MFA code.

image

The environment template of ECS instances, which contains the operating system and pre-installed softwares. Image types include public images, custom images, shared images, and image market. Images are used to create new ECS instances or change the system disks of ECS instances.

Image Processing

An extended service of Object Storage Service (OSS). It is built on OSS and provides real-time image processing functions, such as resizing, cropping, reformatting, and adding watermarks to images. You must enable image processing in the OSS console first, and then call the RESTful

interface provided by the image processing service to process the images stored on OSS, and obtain the processed images immediately.

IMG

image sharing

The action that allows you to share your custom image with other Alibaba Cloud accounts. Then, these accounts can use the shared custom image to create instances and change the system disk.

inbound traffic

Traffic that comes inside your machine.

incremental backup

A type of backup that only copies files that have changed since the previous backup.

incremental data migration

A type of data migration. It synchronizes the incremental data from the source instance to the target instance during the migration process. If you select both full data migration and incremental data migration when you create a migration task, DTS first performs static snapshot on the source instance, migrates the snapshot data to the target instance, and then synchronizes the incremental data written to the source instance to the target instance during the migration process. Incremental data migration is a process of real-time data synchronization between the source and target instances. It does not end automatically. If you want to terminate the migration, terminate it manually on the console.

incremental migration

A type of data migration. It synchronizes part of data changes (addition, deletion, and modification) in a certain period from the source system to the target system to ensure data consistency. In some systems, transactional tables are locked during dynamic incremental migration, causing a data write failure during the migration. Exercise caution when using dynamic incremental migration.

information cube

Behavior analysis: Displays time-based distribution frequency of an event.

Infrastructure as Code

The process where you can perform operations on Alibaba Cloud resources by using templates, APIs, and SDKs, which is similar to writing codes.

IaC

Ingress

A collection of rules that authorize the inbound access to the cluster. You can provide the externally accessible URL, Server Load Balancer, SSL, and name-based virtual host by using the Ingress configurations. You can request Ingress by posting Ingress resources to API servers. Normally, the Ingress Controller is used to implement Ingress by using Server Load Balancer. It can configure the edge router and other front-ends, which helps you handle the traffic in the HA method.

InnoDB buffer pool

InnoDB keeps a buffer pool in its memory for data buffer and index. The buffer pool is divided into two sections, section of sublist of new blocks (frequently visited data-hot data), section of sublist of old blocks (infrequently visited data). When the user visits data and the data is available from buffer pool, it is returned directly, otherwise the disk data will be loaded to the buffer pool of sublist of old blocks section first and then move to the sublist of new blocks section. The data from sublist of old blocks section get flushed according to its access frequency through LRU.

instance

An independent resource entity that contains basic resource elements.

instance ID

The ID for the instances you have purchased. It can be viewed on the console. KVStore for Redis limits connection quantities, bandwidth, CPU specifications, and other aspects based on capacity specifications of individual corresponding instances.

instance type

The type of instance. Each instance provides customer with relevant computing ability according to certain specifications.

intelligent data R&D

The system can perform optimal data calculation and storage based on user input to automatically implement data R&D.

interface

A shared boundary across which two or more separate components of a computer system exchange information. The exchange can be between software, computer hardware, peripheral devices, humans and combinations of these.

Internet

Also known as WAN, wide area network, the global system of interconnected computer networks that use the Internet protocol suite (TCP/IP) to link devices worldwide. It is a network of networks that consists of private, public, academic, business, and government networks of local to global scope, linked by a broad array of electronic, wireless, and optical networking technologies. The Internet carries a vast range of information resources and services, such as the inter-linked hypertext documents and applications of the World Wide Web (WWW), electronic mail, telephony, and file sharing.

Internet Gateway

The ID used to identify a document. The index, type, and ID of a document must be unique. The ID is automatically generated if not provided.

IGW

Internet Protocol

The principal communications protocol in the Internet protocol suite for relaying datagrams across network boundaries. Its routing function enables networking, and essentially establishes the Internet.

IP

intranet

The network within an organization. It is usually a local area network (LAN). A LAN is a computer communication network that interconnects computers, external electronic devices, and databases within a limited geographical area. The LAN is connected to the databases, LANs, or processing centers in other regions by using data communication networks or dedicated data circuits, which forms an information processing system that covers a wide geographic area.

invocation method

The method to invoke the function, mainly in form of C, Pascal.

Input/Output Operations Per Second

- The total number of Input/Output Operations Per Second (when performing a mix of read and write tests). An I/O performance measurement for computer storage devices is frequently mischaracterized as a benchmark, however, IOPS numbers do not relate to real-world application performance.
- The request counts for read/write the instance within one second. Also the maximum counts of read/write to the block device per second, in unit of 4KB.

IOPS

J

Job Scheduler

Distributed resource management and task scheduling system. The field counterparts are many, such as Kubernetes.

K

Keepalived

An open-source software that guarantees the high availability of clusters and detects the status of Web servers. If it detects that a Web server is down or has an error, the Web server is automatically removed from the system. The removed Web server is automatically added after resuming the normal work.

key pair

Public-key cryptography, or asymmetric cryptography, is a cryptographic system that uses pairs of keys: public keys which may be disseminated widely, and private keys which are known only to the owner. The generation of such keys depends on cryptographic algorithms based on mathematical problems to produce one-way functions. Effective security only requires keeping the private key private; the public key can be openly distributed without compromising security.

Kubernetes

An open-source and large-scale container orchestration and scheduling system of Google. It is used to automatically deploy, expand, and manage containerized applications. It is portable and scalable, and can perform automatic scheduling.

K8s

Kubernetes cluster

A cluster used for running Kubernetes applications. It is a private cluster and invisible to other users, which guarantees the safe isolation between your container applications and those of other users.

Kubernetes node

Nodes in Kubernetes clusters that provide the computing power and are the active servers where all the pods are running. The active servers can be hosts or VMs. Containers running on the Kubelet management nodes must run on the active servers.

Kubernetes service

The basic operation unit of Kubernetes. An abstract of real application services, each service has multiple containers to provide the support. The port of Kube-Proxy and service selector determine if the service request is forwarded to the back-end container, and a single access interface is displayed externally. You are not required to know how the back-end works, which brings great benefits to back-end expansion and maintenance.

Kubernetes volume

The volumes in Kubernetes clusters that are similar to Docker volumes. The only difference is that the range of Docker volumes is a container, while the lifecycle and range of Kubernetes volumes are a pod. The volumes declared in each pod are shared by all the containers in the pod. The actual back-end storage technology is irrelevant when you use Persistent Volume Claim (PVC) logical storage. The specific configurations about Persistent Volume (PV) are completed by the storage administrator.

KVStore for Redis

An online storage service that adopts a key-value pair format and is compatible with the open-source Redis protocol. It supports multiple data types, including string, list, set, SortedSet, and Hash, and provides advanced functions such as transactions, message subscription, and message publishing. With the storage method "memory + hard disk", it provides high-speed data read and write capabilities and meets the requirements of data persistence.

L

label

A collection of key-value pairs that are attached to the resource objects. Labels are used to specify the attributes of objects for users. Labels do not affect the kernel systems. You can add a label directly when you create an object or modify the label at any time. Each object can have multiple labels, but the key value must be unique.

label statistics

Label statistics is the information of object node labels in the relational networks. In the Graph Analytics system, labels are divided into two groups: system label and user label. System label is the label defined for nodes of the business system, such as the red list or the black list, while user label is added for system nodes by each Graph Analytics users through the Graph Analytics system.

latency

The delay before a transfer of data begins following an instruction for its transfer.

Layer-4 Server Load Balancer

A service that uses the information defined at the network transport layer (layer 4) as the basis for deciding how to distribute client requests across a group of servers. For Internet traffic, it makes the load balancing policy based on the source and destination IP addresses and ports recorded in the packet header, without considering the contents of the packet.

Layer-7 Server Load Balancer

A service that provides load balancing for services at the application level, such as HTTP services. It determines the routing based on the characteristics of the HTTP header and the actual contents of the message, such as the URL, data type (text, video, and graphics), and information in the cookie.

light-weight configuration center

An Enterprise Distributed Application Service (EDAS) configuration center that can be run locally, which includes the service discovery and configuration management functions.

Linux Virtual Server

A cluster technology that supports the IP load balancing and content-based request distribution techniques.

LVS

listener

A concept used in Server Load Balancer instances. A listener defines how the incoming requests are distributed. You must add at least one listener to a Server Load Balancer instance. It includes front-end ports, back-end ports, Server Load Balancer policies, and health check configurations. Each listener corresponds to a back-end application service.

live migration

Also known as realtime migration. It refers to the process of migrating a running VM or application between different hosts without disrupting its normal operation. Its logic migration procedure is almost the same as that of offline migration. The difference is that live migration results in a very short downtime to ensure that VM can provide services normally. During the early stage of migration, the services run on the source host. When the migration reaches a certain stage, the target host has the necessary resources to run the system. After a transient switchover, the source host takes services over from the target host, ensuring service continuity. For services, users are not aware of the service interruption because the switchover is transient. Live migration applies to scenarios that require high service availability.

locking

The locking mechanism of ApsaraDB for RDS. If the storage space of your instance is full, the system will lock your instance into the read-only status.

log

An abstraction of system changes during the running process. The minimum data unit processed in Log Service. Its content is a time-ordered collection of some operations and the corresponding operation results of specified objects. LogFile, Event, BinLog, and Metric data are its different carriers. In LogFile, each log file is composed of one or more logs, and each log describes a single system event.

log group

A set of logs. The basic unit for reading and writing logs. Log groups can have up to 4096 lines, and can take up to 10 MB in space.

Log Service

A one-stop service for log data, which allows you to quickly complete the collection, consumption, shipping, query, and analysis of log data without the need for development, improve the

Operations & Maintenance (O&M) efficiency and the operational efficiency, and build the processing capabilities to handle massive logs in the data technology (DT) era.

LogHub

The basic function of Log Service, which provides the real-time collection and consumption of logs.

LogHub client library

An advanced mode provided for the LogHub consumers, which is used to solve the issue of automatic shard allocation when multiple consumers consume Logstores simultaneously.

For example, in this mode, logics such as shard load balancing and consumer failover are automatically processed among multiple consumers in the Storm and Spark scenarios. This mode contains four concepts: consumer group, consumer, heartbeat, and checkpoint.

LogHub Log4j appender

An open source project which allows you fine control over the log output destination, and the format and level of each log. You can configure it using a configuration file without need to modify application codes.

LogHub producer library

A LogHub class library written for high concurrency Java applications. The producer library and consumer library are used by LogHub to read and write packaging to lower the threshold for data collection and consumption.

logical backup

The process of using SQL statements to extract data from databases and then saving it in binary files.

LogSearch

The action of real-time index and data query, which allows you to query logs based on time and keywords after creating indexes for LogHub data.

LogShipper

The action of shipping LogHub data to storage services for storage and big data analysis.

Logstore

A unit of Log Service for collecting, storing, and querying logs. Each Logstore belongs to a project and each project can create multiple Logstores.

Logtail

An access service that makes it quick and easy to retrieve logs from servers.

Logtail configuration

It contains the settings for how a Logtail collects logs and processes them, and then determines where the logs are sent to. You can configure a logtail for each Logstore.

M

Machine Learning

Through the Machine Learning service, developers performs analysis and detection of massive data, and predicts the customer behavior and industry trends. Graphic programming enables users drag and drop standard components, connection components, configuration parameters to complete the application development with no need of coding.

Machine Learning Platform for AI

Machine Learning Platform for AI is constructed on layer of MaxCompute. As the machine learning platform integrated with functions of data processing, modeling, offline anticipation, and online anticipation, it provides developers with abundant programming frameworks such as MPI, PS, and BSP, multiple data storage interfaces, and management console for web-based IDE (Integrated Development Environment) and visual experiments.

Managed Security Service

Managed Security Service is the full scope security and consulting service built for the cloud users by Alibaba Cloud security expert based on many years of Alibaba Cloud security experience. It builds and continues to optimize the cloud security defense system and maintains the business security.

Manual Gateway

A user-created dedicated gateway.

MGW

mapping table

A text file that you can read and edit with ease. You can control the infrastructure version by controlling the orchestration template version with tools such as SVN and Git. You can achieve Infrastructure as Code (IaC) by integrating the orchestration capability of ROS with your own applications with APIs and SDKs. The orchestration template also provides a standard way of delivering resources and applications. You can use the template to deliver integrated systems and solutions that include cloud resources and applications.

mass storage

The storage of large amounts of data in a persisting fashion.

Massively Parallel Processing

A distributed shared-nothing computing architecture, where each node is completely independent of other nodes and multiple nodes perform concurrent computing to improve performance.

MPP

master-slave dual node

An instance configured according to master-slave architecture.

max versions

The maximum number of versions that can be stored in the attribute column for data.

MaxCompute

A big data processing platform mainly used for batch structural data storage and processing to provide massive data warehouse solutions and big data modeling.

MaxCompute object

Objects are the basic unit used for MaxCompute user authorization. Users are given operation rights for objects.

maximum version offset

The maximum allowed deviation between the version number of the attribute column and current time, in seconds.

memory

Internal storage where the computing data in CPUs and the data exchanged with external storages, such as devices and hard disks, are temporarily stored.

merge sort

An efficient, general-purpose, comparison-based sorting algorithm.

message key

The business identifier of a message, which is set by the message producer and uniquely identifies a business logic.

metadata

Metadata, also known as intermediate data, or description data. It defines data properties.

metadatabase

The database where data is organized, stored, and managed based on the data structure.

MetaService

A service that allows you to access Alibaba Cloud resources in the E-MapReduce cluster without using AccessKey.

metrics

The variable measured in a time series. For example, a time series of stock prices (the metric) may be called a price curve.

Mongos

The ApsaraDB for MongoDB cluster request entry. All requests are coordinated through Mongos. Mongos forwards data entry requests from ApsaraDB for MongoDB clusters to the corresponding shard server. Multiple Mongos can be selected as the entry request. This prevents ApsaraDB for MongoDB failure caused by one failed ApsaraDB for MongoDB request.

mount point

The address of the file system instance in VPC or classic network. Each mount point relates to one domain name. You can specify the domain name of the mount point to mount the corresponding Apsara File Storage NAS file system to the local system.

multicast

Group communication where data transmission is addressed to a group of destination computers simultaneously and is often employed in IP applications of streaming media.

multipart upload

A method of uploading a large file by separating it into smaller parts.

Multi-Service Transmission Platform

A unified network management platform for multi-service nodes based on SDH, which supports access, processing, and transmission of TDM, ATM, Ethernet, and other services.

MSTP

multi-tenant isolation

A system where the OS or programs are shared by users, but user data is isolated.

multi-zone

An area composed of multiple zones, which is deployed in different regions by Alibaba Cloud Server Load Balancer to achieve disaster recovery across data centers in the same region. If the data center in the active zone malfunctions or becomes unavailable, Server Load Balancer rapidly switches to the data center in the standby zone to restore its service capabilities within 30s. When the active zone is restored, Server Load Balancer automatically switches back to the data center in the active zone to provide services.

multiple zones

An area composed of multiple zones, which is deployed in different regions by Alibaba Cloud Server Load Balancer to achieve disaster recovery across data centers in the same region. If the data center in the active zone malfunctions or becomes unavailable, Server Load Balancer rapidly switches to the data center in the standby zone to restore its service capabilities within 30s. When the active zone is restored, Server Load Balancer automatically switches back to the data center in the active zone to provide services.

N

namespace

A feature that provides virtual isolation for Kubernetes clusters. Kubernetes clusters have three namespaces by default: default, kube-system, and kube-public. Administrators can create new namespaces based on their requirements.

network analytics

Network analysis is to analyze the network graph's position, activity, and relation from different aspects of algorithm, and then highlight the result nodes.

network baseline

Network baseline is a set of the meta data file (currently yaml format) that describes the network topology, network port connection, configuration file of the various network devices. It calculates the detailed solution of the Apsara Stack network solution according to the required input (such as IP pool, product, and server scale).

network device type group

Network device type group is the network device specifications verified and confirmed by Apsara Stack platform, including machine names, hardware configurations, and manufacturer models.

network latency

The objects that exist in the real world, such as human, cell phone number, car. The objects in the Graph Analytics instance require a unique object that is identified by the main key, such as the ID number of human, cell phone number of cell phone, plate number of a car.

network type

A secure, reliable, and cost-friendly cloud storage service provided by Apsara Stack to process a large amount of data. You can call APIs to upload or download data to or from any application anytime anywhere, and perform simple data management through the Web console. OSS can store files of any type from various websites, development-oriented enterprises, and developers.

node

One server (could be virtual instance or physical server) installed with Docker Engine, which can be used to deploy or manage containers; the container Agent program is installed and registered to one cluster. The node count in one cluster is scalable.

O

object

The objects that exist in the real world, such as human, cell phone number, car. The objects in Graph Analytics requires a unique object that is identified by the main key, such as the ID number of human, cell phone number of cell phone, plate number of a car.

Object Storage Service

A secure, reliable, and cost-friendly cloud storage service provided by Apsara Stack to process a large amount of data. You can call APIs to upload or download data to or from any application anytime anywhere, and perform simple data management through the Web console. OSS can store files of any type from various websites, development-oriented enterprises, and developers.

oss

offline computation

A computing process that is performed after the generated data is stored.

open API

The management and control tool provided for customers to realize relevant resource management and operation.

open source

A certification mark registered by and an official definition given by the Open Source Initiative (OSI). Softwares that bear this mark are open source. An open source software can be used, modified, and released without license restrictions, and its source code is available for public use.

open source ecosystem building

Open source ecosystem building includes components like Hadoop, HBase, Spark, Hive, Pig, Swoop, Hue, and Zeppelin. It support monthly and annual payment and pay-as-you-go payment.

open source software

A type of computer software in which source code is released under a license in which the copyright holder grants users the rights to study, change, and distribute the software to anyone and for any purpose. Open source software may be developed in a collaborative public manner. Open source software is a prominent example of open collaboration.

Operating System

Operating System is the system software that manages the computing hardware and software resources.

os

operation log

Operation log is the record of all the operations, including the time and content of each operation.

OSS object

A basic unit for data storage in OSS. An object is a file in OSS. An object consists of the metadata (Object Meta), user data (data), and object name (key). Objects are identified by a key. The key is unique within the bucket.

outbound traffic

Traffic that goes outside your machine.

owner

The person responsible for setting and controlling the permissions of objects, and who can grant such permissions to other users.

P

packet loss

An event where one or more packets of data traveling across a computer network fail to reach their destination.

packet loss rate

The ratio of packets lost with respect to packets sent, generally measured as a percentage value.

page view

The view counts or click rate of certain page. Each visit of the web page is recorded as one count.

Pandora

Pandora is a light weight container (technically known as taobao-hsf.sar). It isolates web apps and middleware, and middleware dependencies, to minimize issues. EDAS Pandora integrates various plugins into the container to enable services such as discovery, configuration pushing, and link-tracing calls. These plugins allow you full management of EDAS applications.

parallel computing

Parallel computing refers to the computing mode in which multiple commands are executed at the same time. In condition that commands are executed simultaneously, the computing process are divided into multiple minor parts and processed in parallel computing mode.

peak bandwidth

The maximum permitted traffic burst that a site can sustain.

performance

The amount of useful work accomplished by a computer system. Outside of specific contexts, computer performance is estimated in terms of accuracy, efficiency and speed of executing computer program instructions.

permission group

A group that defines access permissions based on a whitelist (IP addresses or network segments). It is used to control access to Apsara File Storage NAS. Each mount point must be bound to a permission group.

persistent connection

A connection used to send multiple data packets continuously. During the connection, both parties must send link detection packets if no data packets are sent.

Persistent Volume

A storage resource provider that varies with the infrastructure of clusters. PVs are configured by the administrator of Kubernetes clusters.

PV

Persistent Volume Claim

A storage resource user that varies with the requirements of business services. PVCs are configured by the user (namely, service administrator) of Kubernetes clusters.

PVC

physical backup

Dump of physical files, such as data files, control files, and archived logs. These files can be used to restore abnormal databases.

plugin

The system provides many built-in plugin to help you process imported data. You can select a plugin by using content conversion when defining application structures or configuring data sources.

pod

The smallest deployment unit and metering unit of Kubernetes. It is consisted of one or more containers based on different scenarios. If it contains multiple containers, these containers share

its computing resources, storage space, IP addresses, and ports. You can limit the usage ratio of the computing resources for these containers. For stateless applications, it can be deleted and created at any time. If it malfunctions, the system deletes it and creates a new one to keep its total number in the service unchanged, achieve elastic recovery of errors, and not affect the service availability.

project administrator

The manager of the data project space.

port

A port is an endpoint of communication in computer networking. This can be hardware port, a logical port, or both. TCP and UDP ports are identified by their port number (an integer from 0 to 65535).

port forwarding

A method provided by SSH for secure network communications. It forwards the behavior of a network port from one network node to another. It allows an external user to access a port of a private internal IP address from the external by passing an activated NAT router.

pre-check

A mandatory phase before the start of a migration task. It checks the preconditions that will affect the migration, such as connectivity of the source instance, and the permissions of the migrating account. If it fails, make the appropriate changes and try again.

pressure test

Pressure test is the test method that verifies the system stability. Normally the test covers scenarios that are out of normal condition to observe the function extremes and hidden risks.

primary key

The unique identifier of each row in a table. It consists of one to four primary key columns. When a table is created, the primary key must be defined. To define a primary key, provide the column name and data type of each primary key column, and the fixed sequence of the primary key columns. The data types of the primary key column can only be String, Integer, and Binary. For a primary key column of String or Binary data type, the size of the column value must not exceed 1 KB.

private key

The unique identifier of each row in a table. It consists of one to four columns. When a table is created, the primary key must be defined. To define a primary key, make sure that the name and data type of each primary key column, and the fixed sequence of the primary key columns are available. The data types of primary key columns can only be String, Integer, and Binary. If the data type is String or Binary, the size of the column value cannot exceed 1 KB.

private network

The internal network used for VM instance connections.

private-read-write

An access control permission level for OSS buckets and objects. The access control permissions include public-read-write, public-read, and private. The private permission allows only the creator of the bucket to read and write objects in the bucket. Other users cannot access the objects in the bucket.

process number

The session count. Session is the operation activity of the computing program related to one data set. It is the basic unit of system resource allocation and scheduling and also the basic unit of operation system.

product baseline

The deployment meta data of Apsara Stack products. It contains a suite of software components and the standard mode for hardware compliance. The Apsara Stack team, including PD from various product line, R&D developers define the format of the product baseline and the Shuguang team verifies and finalizes the product baseline. Each Apsara Stack version corresponds to one suite of product baselines.

Product Introduction

Product Introduction is the key part of product documents and explains the product family to which the product belongs.

product summary

The overview and summary about what a product is, what it does, and how it works.

programming model

A style of programming where execution is invoked by making what appear to be library calls.

project

The project is the resource management unit in Log Service and is used to isolate and control resources. You can manage all the logs and the related log sources of an application by using projects. Projects manage the information of all your Logstores and the log collection machine configuration, and serve as the portals where you can access the Log Service resources.

project space

Project space is the basic business organization unit for Alibaba Cloud Realtime Compute. It is the basic unit of user management for clusters, tasks, resources, and personnel.

project version

Project plans are not completed at once. After multiple solution comparison and involvement of different solutions, the final solution is sealed. Therefore, each project version relates to a set of independent plan and implementation solution. Each available version is named as backup and the version that customer selects is the finalized version.

proprietary intellectual property right

Ownership of intellectual property which may include financial information, intellectual property (concepts, designs, techniques), technical documentation, artwork, and the contents which are protected under law.

public address

A connection address to access a host on a public network. Public addresses are assigned by InterNIC and consist of class-based network IDs or blocks of CIDR-based addresses that are guaranteed to be globally unique to the Internet.

public data center

The data center that abstracts public topics from all service data to develop standardized and shareable data.

public parameter

Public parameter is the parameter that is required by each interface.

public request parameter

Request parameters used for all interfaces

public return parameter

Each time you send an interface call request, the system returns a unique identification code (RequestId) regardless of whether the request is successful or not.

public-read

An access control permission level for OSS buckets and objects. The access control permissions include public-read-write, public-read, and private. Public-read allows only the creator of the bucket to write objects to the bucket. Anyone else (including anonymous users) can only read objects from the bucket.

public-read-write

An access control permission level for OSS buckets and objects. The access control permissions include public-read-write, public-read, and private. Anyone (including anonymous users) can read and write objects from the bucket. Any costs incurred by these operations are borne by the creator of the bucket. Exercise caution when using this permission.

push

A proactive action to send resources from the origin site to edge nodes. You can directly hit cache when accessing resources, which lightens the pressure of the origin site caused by bursts in the traffic back to the origin.

Q

Query Per Second

Query Per Second is a common measure of the amount of search traffic an information retrieval system, such as a search engine or a database, receives during one second.

QPS

Quick BI

A new generation of Business Intelligence service on the cloud.

R

rack

A physical steel and electronic framework that is designed to house servers, networking devices, cables and other data center computing equipment. This physical structure provides equipment placement and orchestration within a data center facility. It generally measures 42U in height.

rate limiting and throttling

Control of the maximum system traffic volume by adjusting the traffic threshold or proportion to guarantee the safe and reliable running of the system. If the front-end website has large volumes of traffic, you can control the traffic to prevent the large volumes of traffic from damaging the back-end core systems, which guarantees the service availability.

RDS Operations and Maintenance System

The operations and maintenance system of ApsaraDB for RDS.

read timeout

When calling a constructor using the SDK, it specifies the period of time that the SDK waits when attempting to read data from an API response before timing out.

read weight proportioning

The proportional load balancing of read-only instances in ApsaraDB for RDS to achieve real-time read throttling.

read/write capacity unit

The smallest billing unit for data read and write operations. A read/write capacity unit (CU) is 4 KB. The read or written data volume that is smaller than a CU is rounded up. For example, writing 7.6 KB data is counted two write CUs. Reading 0.1 KB data is counted as one read CU.

read-only instance

An instance type in which data in the instance can be accessed but not modified. There are two types of physical database types based on whether the write is allowed: the primary instance that allows read and write and the read-only instance that only allows read. The primary instance applies to the primary MySQL instance in Apsara Stack and primary ApsaraDB for RDS instance in Alibaba Cloud public cloud. The read-only instance applies to the secondary MySQL instance in Apsara Stack and ApsaraDB for RDS instances in Alibaba Cloud public cloud.

Realtime Analytics

Realtime Analytics refers to the analysis of parameter process time during a dynamic process during the operation.

Realtime Application Monitoring Service

A text file that you can read and edit with ease. You can control the infrastructure version by controlling the orchestration template version with tools such as SVN and Git. You can achieve

Infrastructure as Code (IaC) by integrating the orchestration capability of ROS with your own applications with APIs and SDKs. The orchestration template also provides a standard way of delivering resources and applications. You can use the template to deliver integrated systems and solutions that include cloud resources and applications.

realtime computation

Compute during data generation.

Realtime Compute

A common stream compute platform that provides Realtime Compute service. Realtime refers to within seconds or even milliseconds.

Recovery Point Objective

The amount of data at risk, which is determined by the amount of time between data protection events and reflects the amount of data that potentially could be lost during a disaster recovery.

RPO

recursive analysis

Domain resolution service through local cache query and service system of authority resolution. Recursive resolution resolves internet domain names.

Redis database

A cloud-based version of Redis. KVStore for Redis is an open-source in-memory database that implements a distributed, in-memory key-value store with optional durability. It supports 256 databases. By default, it writes to the first database.

reference manual

A help document for users. It contains all reference contents that users need to know when they use the product.

region

Different regions are geographically far apart from each other, perhaps in different cities. Each zone belongs to certain region.

relation

The interactive relation between objects. In Graph Analytic, relation refers to the associations between objects, such as the phone calls and messages are relations between mobile accounts,

while relation between the user and the mobile account is the fact that the mobile accounts belongs to the user.

relation analysis

An analysis method that focuses on mining small numbers of relevant clues and intelligence from large amounts of unrelated information. It is a process of converting information into actionable intelligence. It helps you implement the unlimited association of information.

relation detail list

Displays the specific attribute of relations for one or more objects.

relational network analytics

The visualized data analysis platform for big data based on relation network. It is applied in risk control business such as anti-theft, anti-cheating, anti-money laundering. It detects the scenarios according to internet industry data clues, such as anti-cheating marketing, false transaction judgement and research, anti-insurance fraud, enterprise internal auditing, and enterprise relation analysis.

release cluster

An operation that releases a cluster. You can release a cluster after offline jobs are completed. You can also dynamically add nodes.

remote logon reminder

Server Guard analyzes and compares logon logs on the cloud. An alarm is triggered when Server Guard detects an unfamiliar remote logon.

Replica Set

The upgraded version of Replication Controller (RC). Compared with RCs, RSs support more selector types. RS objects are not used independently, but are used as the deployment parameters in the ideal status.

RS

Replication Controller

A feature that ensures that a specified number of pod replicas are running in the Kubernetes cluster at any time. It achieves this by monitoring the number of running pods. One or more pod replicas can be specified. If the number of pod replicas is smaller than the specified value, an RC

starts new pod replicas. If the number of pod replicas exceeds the specified value, the RC stops the redundant pod replicas.

RC

required parameter

The required parameter as defined by Alibaba Cloud.

reserved read throughput

A table attribute. Table Store reserves certain resources for access. The access within the reserved read throughput consumes less resources.

reserved read/write throughput

An attribute of table. Table Store reserves certain resources for access. The access within the reserved read/write throughput consumes less resources.

reserved write throughput

A table attribute. Table Store reserves certain resources for access. The access within the reserved write throughput consumes less resources.

resize

A method used to scale up the capacity of a disk attached to an ECS instance.

resize cluster

You are allowed to resize your cluster horizontally when your cluster resources (such as computing resource and storage resource) are not sufficient.

Resource Orchestration Service

A service that provides developers and system managers with a simple method to create and manage their Alibaba Cloud resources.

ROS

restart

The process by which a running computer system is restarted, either intentionally or unintentionally.

role

A set of permissions. It is generated when a dimension is associated with foreign keys to produce a star or snowflake model. One role is generated every time a same dimension is associated with different tables. When a dimension is associated with two foreign keys in a logical table, different aliases are required to uniquely indicate the roles of this dimension in the table.

rollback

The action of restoring a disk to a state and setting from a previous point in time.

Round-Robin scheduling

A scheduling algorithm that Server Load Balancer uses to distribute the traffic. Requests are sequentially distributed to the back-end servers.

RR

route calculation

A calculation method that powers routing protocol functions and reduces routing overhead.

route entry

Each item in the route table, which defines the next hop address for the network traffic destined to a specific destination Classless Inter-Domain Routing (CIDR) block.

route table

A list of route entries in a VRouter.

RPS

The number of SQL statements performed each second, including begin, commit, insert, delete, and create table.

rule engine

An online service for scenarios where the business rules change frequently. It helps you separate business rules from the application code. It combines predefined conditional factors to compile business rules flexibly and then makes business decisions based on the business rules.

running

The normal operating status of instances. You can run your services on instances that are in this status.

S

scaling activity

An activity generated after scaling rules are successfully triggered. The activity is mainly used to describe the changes of Elastic Compute Service (ECS) instances in the scaling group.

scaling configuration

It defines the configurations of Elastic Compute Service (ECS) instances used for Auto Scaling.

scaling group

A collection of Elastic Compute Service (ECS) instances with the same scenario. It defines the maximum and minimum number of ECS instances in the group, associated Server Load Balancer instances, ApsaraDB for RDS instances, and other attributes.

scaling rule

Rules that define the specific scaling in or out operations, such as adding or removing N Elastic Compute Service (ECS) instances.

scaling trigger task

A task that triggers the scaling rules, such as the timing tasks and alarm tasks of CloudMonitor.

scenarios

Narrative of foreseeable interactions of user roles and the technical system, which usually includes computer hardware and software.

schema migration

A type of migration. In database migration, it refers to the migration of schema definitions including tables, views, triggers, stored procedures, and storage functions. For migration between heterogeneous databases, the data type mapping is carried out in the schema migration phase, and the object type is changed to the appropriate target type. For example, when Oracle is migrated to MySQL, the number type in Oracle is mapped to the decimal type in MySQL.

schema update

An update that modifies the schema definition such as create table, alter table, and drop view.

Users can choose whether to subscribe to schema updates when creating a subscription channel.

Secure Shell

A cryptographic network protocol for operating network services securely over an unsecured network. Typical applications include remote command-line login and remote command execution, but any network service can be secured with SSH.

SSH

security group

A virtual firewall with status check and filtering function to configure the network access control for one or more cloud servers. Instances within one security group are interconnected. Instances across security groups are not connected by default. Users are allowed to authorize the connection between security groups.

security group input rules

A set of rules that enable or disable the Elastic Compute Service (ECS) instances associated with the security group to access the Internet or intranet from the inbound direction.

security group output rules

A set of rules that enable or disable the Elastic Compute Service (ECS) instances associated with the security group to access the Internet or intranet from the outbound direction.

security vulnerability detection

A system that scans and analyzes systems and detects the vulnerability of these systems based on scans of databases. It also includes a security mechanism to determine if any new vulnerabilities are present.

segment

The basic unit of computing resource.

selected analysis

Users search for the object according to self-defined geological position and space.

separate attach

Operation of attaching disks to any ECS instance in the same zone is supported.

sequence analysis

Display details of each event in sequence of time.

server

An application that agrees to request-side connections and sends responses. Applications can act as both a client and a server.

server differentiation

The machine models in the server group are differentiated into multiple hardware groups. The purpose of doing so is to match each application with proper server models after the product baseline is finalized.

Server Guard

A component of Apsara Stack Security to manage the safety of servers. Server Guard updates with the rules of the protection center of Alibaba Cloud through the server-side light-weighted agent plugin, and matches information collected from the client for analysis to provide realtime defense against attempted intrusions.

Server Load Balancer

A concept of Server Load Balancer instances, which includes front-end ports, back-end ports, Server Load Balancer policies, and health check configurations. Each listener corresponds to a back-end application service.

SLB

Server Load Balancer monitoring

A function of listening to the ports, load balancing policies, and health check configurations.

server model group

The server specifications verified and confirmed by the Apsara Stack platform, including machine brand, hardware configuration, and manufacturer model number.

service

- A set of containers based on the same base image and configurations as a scalable microservice.
- The basic operation unit of Kubernetes. It is an abstract of real application services. Each service has multiple containers that support it. The Kube-Proxy port and service selector determine whether the service request is forwarded to the back-end container, and a single access interface is displayed externally. The back-end operations are invisible to users.

Service Call Monitoring

An Enterprise Distributed Application Service (EDAS) monitoring function. It can fully monitor the service QPS, response time, and error rate for the service calls of the application.

session persistence

A basic function of Server Load Balancer that distributes access requests from the same client to the same back-end server for processing.

shard hash key range

High-performance Key-Value storage system (cache and store) is developed by BSD open-source protocol.

shared block storage

A block-level data storage device that supports concurrent read/write access of multiple Elastic Compute Service (ECS) instances and features high concurrency, high performance, and high reliability. Its data reliability reaches 99.9999999%. A single shared block storage can be attached to at most four ECS instances simultaneously.

short-lived connections

A connection created when both parties have data exchanges. The connection is closed after the data is sent. The data transmission occurs only once for each connection.

signature

A distinctive pattern, product, or characteristic by which someone or something can be identified.

signature mechanism

ECS service verifies each access request. No matter the request is with HTTP or HTTPS protocol, the response has to include signature information.

Single Point Of Failure

A part of a system that, if it fails, will stop the entire system from working.

SPOF

single-connection

The mode in which only one client is connected to a database. In this mode, data of 1 KB, 10 KB, 100 KB and 800 KB is used to perform read/write operations on Memcached and OCS, and the average response time of Memcached and OCS are compared.

SLB instance

An instance running the Server Load Balancer (SLB) service.

snapshot

A copy of data on a disk at a certain point in time. There are two types of snapshots: automatic and manual snapshots.

snapshot quota

A quota limit for each disk. Each disk in Elastic Compute Service (ECS) can create at most 64 snapshots.

Software Defined Network

A method that separates the control level of network devices from the data level to flexibly control the network traffic and provide a good platform for the innovation of core networks and applications.

SDN

Software Development Kit

A collection of development tools used by software engineers when creating application software for a specific software package, software framework, hardware platform, or operating system.

SDK

Source Network Address Translation

It translates the source address of an IP packet to another address.

SNAT

specification

The measure of the performance of different link specifications to the number of simultaneous records.

split

The action used to divide an object. Shard split is an operation that splits a shard into two shards connected by a shard key range.

SQL injection

A type of attack that injects malicious SQL statements into a submitted web form, or a query string into a domain name or web page to deceive servers into executing malicious SQL statements.

SSD cloud disk

A Solid-State Disk (SSD) that is installed on the Elastic Compute Service (ECS) instance, oriented to the I/O-intensive applications, and provides stable and highly random IOPS performance.

SSH key pair

A new authentication method provided by Alibaba Cloud that allows you to log on to the Elastic Compute Service (ECS) instances remotely.

stack

A logic concept, the customized resource template file. The resource stack is the resource executed by Resource Orchestration Service (ROS). One resource stack represents one user operating system.

starting

The status of an instance when it is started or restarted in the console or by using an API until the instance runs normally. An exception occurs if an instance stays in this status for a long time.

statement

A syntactic unit that consists of a word or a group of syntactically associated words to express propositions, doubts, commands, wishes, or exclamations.

static website

A website with web pages composed of fixed content, including scripts (such as JavaScript) that are executed by the client without the need for prior web programming or database design.

static website hosting

Users can set their own bucket to the static website hosting mode. After the static website hosting mode is configured, the bucket can be accessed as a static website, and users can be automatically redirected to the index page or error page.

static/dynamic resource separation

Separation of static and dynamic resources from Web pages or mobile applications.

stop scheduling

An operation that stops data scheduling. Tasks are not started at the specified time point.

stopped

The status of an instance after it stops normally. An instance in this status cannot provide external services.

stopping

The status of an instance after the stop operation is performed in the Apsara Stack console or by using an API until the instance actually stops. An exception occurs if an instance stays in this status for a long time.

storage

A service that is used to store information or data in a specific format in a specific medium built in or out of a computer. Meanwhile, valid access to the medium is guaranteed.

storage engine

A component of the MySQL database that manages how data is stored in files or memory. Each storage technology adopts a different storage mechanism, indexing technique, and locking mechanism. A storage technology provides a unique set of features and capabilities. You can select different storage technologies to obtain additional features such as improved data processing capabilities, improving the overall performance of your applications.

subscription channel ID

A unique identification of a subscription channel. After you purchase a subscription channel, Data Transmission Service (DTS) automatically generates a subscription channel ID. When you use the SDK to consume incremental data, you need to configure the appropriate subscription channel ID. The subscription channel ID corresponding to each subscription channel is displayed in the subscription list of the DTS console.

subnet mask

For IPv4, a network may also be characterized by its subnet mask or netmask, which is the bitmask that when applied by a bitwise and operation to any IP address in the network, yields the routing prefix. Subnet masks are also expressed in dot-decimal notation like an address. For example, 255.255.255.0 is the subnet mask for the prefix 198.51.100.0/24.

super administrator

The owner in tenants with highest authority.

synchronization latency

The difference between the timestamp of the target instance in the source library, and the current timestamp of the homologous instance.

synchronized records per second

The number of records synchronized to the target instance per second (unit: RPS). Synchronized RPS is the specification by which the data synchronization service is sold.

syntax tree

A tree representation of the abstract syntax structure of source code written in a programming language. Each node of the tree represents a structure in the source code.

system disk

A disk that contains an operating system.

T

Table Store

A NoSQL-based Apsara Stack storage service that features high concurrency and low latency. Table Store is capable of processing a large amount of data.

tag

An identifier used to classify and manage ECS instances.

task

A job consists of tasks and their dependencies. Batch computing supports jobs that can be described in the form of a Directed Acyclic Graph (DAG). The dependencies between tasks can only be specified when the job is submitted, and cannot be modified after the submission is completed.

task scheduling

Task scheduling is a crucial component of the operation system. For realtime operation system, task scheduling affects the performance.

TCP retransmission

The resending of TCP packets that have been damaged or lost during transmission. TCP handles a retransmission by setting a timeout when it sends data, and if the data isn't acknowledged when the timeout expires, it retransmits the data.

temporary table

A table that exists at the session level. Temporary tables are only visible to the session in which they were created and are automatically dropped when that session logs off, generally when the VFP exits. Temporary tables offer a performance benefit because their results are written to local storage, rather than remote storage.

Tesla

O&M system of Table Store (formerly OTS).

thermal display

Thermal display shows the density distribution of the objects on a map. It is divided into thermal display and legacy thermal display.

thread

A separate server that handles a subset of the overall workload. The ApsaraDB for MongoDB uses sharding for horizontal scaling of databases.

Threat Detection Service

A service that collects more than 20 types of raw logs and cybersecurity threat intelligence reports from multiple enterprises. It uses machine learning to reconstruct past attacks and predict potential future attacks.

three centers in two locations

A 3-redundancy system where two data centers are physically located in one city or equivalent area, however, the third data center must be physically located more than 1000 km away from the other two centers.

threshold

A function of mapping a domain name to a corresponding IP address based on DNS.

throughput

The amount of data successfully transmitted through a network, device, port, virtual circuit, or another facility within a given time.

time granularity

A data unit exchanged and transmitted in a network, that is, a data block to be sent by a site at one time.

Time To Live

A feature for attribute column data. If the data version is greater than the time to live, the data is expired.

TTL

topic

A level-1 message topic. It is used to classify messages.

tracing path

A computer network diagnostic tool for displaying the route (path) and measuring transit delays of packets across an IP network

traffic scrubbing

A service used to monitor the data flow coming into your Internet Data Center (on-premises data center) in real time and identify the abnormal flow, such as DoS attacks, in time. Abnormal flow is cleaned without affecting the normal services.

Transmission Control Protocol

A connection-oriented and reliable transport layer communication protocol that is based on byte streams.

TCP

Transparent Data Encryption

Real-time I/O encryption and decryption of the entire database (including data and log files). It is completely transparent to applications and does not require any modifications to existing applications.

TDE

trigger

A method that the SQL server provides for programmers and data analysts to guarantee the data integrity. It is a special storage process related to table events. It is initiated by events, not called by programs or started manually. For example, when a table is inserted, deleted, or updated, a trigger is initiated. The trigger is typically used to reinforce data integrity and business rules.

trojan

Attackers gain access to the administrator account through SQL injection, server and zero-day vulnerability exploits, and sensitive file scanning. After gaining back-end access, attackers can obtain a webshell through database backup and recovery, or uploading vulnerabilities. Attackers then use the webshell to modify web page content by embedding malicious code into the web page. Attackers can also exploit weak passwords to gain access to the server or FTP, and directly modify the web page content. When accessing web pages embedded with malicious code, users will automatically be redirected to a malicious URL or download the Trojan.

trusted cloud

A program of the Cloud Security Alliance industry group created to help cloud service providers develop industry-recommended, secure and interoperable identity, access and compliance management configurations and practices. Alibaba Cloud is the first cloud services provider to obtain the CSA STAR gold medal certification.

Tubo

Statistics: Displays statistics about relationships and entities in relational networks, including overall distribution, object familiarity, and relationship attributes.

two centers in one location

The action of deploying two data centers in the same geographic area, one acting as the production center and one acting as the disaster recovery center. This ensures highly-effective disk data synchronization and asynchronous backup is performed between the centers to minimize impacts to availability.

U

ultra cloud disk

A cloud disk that combines Solid-State Disk (SSD) and Hard Disk Drive (HDD) as the storage media.

Unity3D

An integrated game development tool compatible with multiple platforms. A fully integrated and professional game engine. Developed by Unity Technologies, this tool allows a player to easily create various interactive contents such as 3D video game, architectural visualization, and realtime 3D animation. Its logs can be collected conveniently by using the Web Tracking function of Log Service.

URL forward

The action of automatically redirecting you to a preset address when you access a domain name. It includes explicit and implicit URL forwarding.

User Datagram Protocol

In computer networking, the User Datagram Protocol (UDP) is one of the core members of the Internet protocol suite. The protocol was designed by David P. Reed in 1980 and formally defined in RFC 768. With UDP, computer applications can send messages, in this case referred to as datagrams, to other hosts on an Internet Protocol (IP) network. Prior communications are not required in order to set up communication channels or data paths.

UDP

V

verification

A process that verifies a result.

vertical data center

A data center that stores raw data from different business databases.

Virtual Boarder Router

The mapping of your leased line in VPCs. It can be regarded as a VRouter, or a forwarding bridge between an on-premises data center and a VPC.

VBR**Virtual Extensible LAN**

A VXLAN-based layer-2 network. A single VXLAN belongs to a large VXLAN network pool.

VXLANs are isolated from each other at layer-2.

VXLAN**Virtual Local Area Network**

An emerging data exchange technology that logically divides Local Area Network (LAN) devices into segments to implement the virtual work group.

VLAN**virtual network layer**

The network where the Elastic Compute Service (ECS) instances reside. It avoids the limits of physical network layer. User logic and transmitted contents at the virtual network layer are invisible to the physical network layer, and the physical network layer does not parse the transmitted information at the virtual network layer, which protects the user privacy. The virtual network layer is completely implemented by using softwares. The separation between data layer and control layer, path decision, and policy delivery are completed by the controller at the virtual network layer. Therefore, the Software Defined Network (SDN) is implemented.

Virtual Private Cloud

The custom private network created based on Alibaba Cloud. Full logical isolation is achieved between VPCs. You can create and manage cloud product instances, such as Elastic Compute Service (ECS), ApsaraDB for RDS, and Object Storage Service (OSS), in your created VPC.

VPC**VNC**

A function in the Alibaba Cloud console, which is used to connect to the Elastic Compute Service (ECS) instances if common remote connection tools, such as PuTTY, Xshell, and SecureCRT, are unavailable.

VRouter

A networking hub that uses Linux-specific VM instances to implement multiple network services.

VServer group

A group of back-end servers that can be customized and managed in the listener dimension. They allow listeners under an SLB instance to distribute different requests to different back-end servers depending on the configured forwarding rule.

VSwitch

A basic network device of Virtual Private Cloud (VPC), which can connect to different cloud product instances and must be specified when you create a cloud product instance in VPC.

W

weak password

Weak passwords are passwords that are easy to be decrypted, mostly simple combinations of numeric digits, digits that are the same with the account name, keys that are close to each other on the key board, or common names, such as "123456", "abc123", "Michael". Universal passwords of terminals newly shipped from factories also belong to weak password.

Web Application Firewall

A cloud firewall service that detects and blocks web attacks to guarantee website security based on data mining.

WAF

web vulnerability detection

The process of testing a web application's susceptibility to malicious tampering or other illicit activity through the means of scanning remote and local systems.

webshell

A segment of web codes (mostly the ASP and PHP codes) running on the server. Attackers perform malicious operations on the server by using this segment of codes to obtain sensitive technical information or gain the control over the server by penetration and privilege escalation.

WebTracking

A function that Log Service uses to support collecting logs from HTML, H5, iOS, and Android platforms and customizing dimensions and metrics.

weight

A relative value that indicates the importance of the index in the overall evaluation.

Weighted Least Connections

A scheduling algorithm that Server Load Balancer uses to forward traffic. In addition to the weight set to each back-end server, the actual loads (number of connections) of the back-end server must be considered. If the weights of the back-end servers are the same, a new request is sent to the server with the fewer connections.

WLC

Weighted Round Robin

A scheduling algorithm that Server Load Balancer uses to forward traffic. Back-end servers with higher weights receive more requests than those with lower weights.

WRR

whitelist

An access control method. When a user is added to the whitelist, the user is permitted access. Users who are not on the whitelist are not permitted access. The opposite of a blacklist.

work space

A container of Quick BI objects, such as data portals, spreadsheets, dashboards, data sources, and datasets. Multiple users can access the same workspace to facilitate collaboration.

workbook

A spreadsheet that organizes your data into rows and columns in a clear, instantly readable format.

Z

zone

The reference to a physical, isolated area with an independent power grid and network in a region. Each zone in a region is isolated, but the network latency for resources within the same zone is lower than across zones. Intranet communication can take place between resources in different zones of the same region, and fault isolation can be performed between zones. Deployment of resources in the same zone depends on the requirements for disaster recovery and network latency.

zone-disaster recovery

A redundancy system where two data centers are physically located in one city or an equivalent area, and are at least 1,000 km apart.

zone-disaster recovery and backup

Zone-disaster recovery and backup is the local backup of the production data in the zone-disaster recovery data center. It features by its high speed, but cannot guarantee the availability of the data and system in the local backup data center in case of severe disaster.